


HEAT RECOVERY VENTILATION UNIT CFV



AIRVENTS CFV, CFV-HE, CFV-HW

The brand new premium line of commercial heat recovery air handling units for floor mounting with high-efficient counter-flow heat exchanger. Available in five standard sizes based on the air flow capacity of 1500, 2500, 3500, 5000 and 6000 m³/h. Optionally accomplished with no heater (CFH series), electric heater (CFH-HE series) or water heater (CFH-HW series) and ready for operation with all necessary control elements.





Main features:

- High-efficient EC fans, backward-curved, external rotor. Low power consumption at any speed, low noise level and stable operation in any climate conditions.
- Integrated plug-and-play controls on the basis of the Carel kVent. controller. Easy connecting via web-interface using the Ethernet-Modbus and BACnet.
- Insulated double-skin frameless casing.
- High-efficient counter-flow heat exchanger is made of profiled aluminium plates and impregnated with elastic heat-resistant sealant.
- The stainless steel drain pan is located on the inlet and outlet sides.
- The casing panels are made of steel with zinc-aluminium coating and internally lined with 40 mm heat- and sound-insulating mineral wool layer. The units have C4 corrosion resistance class in compliance with ISO 12944. Each model is available in left- and right-handed modifications. The units have service access on both sides and on the bottom.
- Washable F7, G4 (optional) panel filters in exhaust and supply air streams.
- Integrated control panels:
 - A30 th-Tune: standard control panel with handy interface ensures basic setup of parameters.
 - A32 pGDe: control panel with expanded functionality ensures complete setup of parameters.
- Integrated 100 % bypass of the heat exchanger with automatic damper and Belimo actuator ensures active freeze protection. Free heating and cooling functions are also available. Built-in automatic external air dampers with Belimo actuators.
- ECO-Design'18 compliant.

Technical parameters



Model		CFV 1500	CFV 2500	CFV 3500	CFV 5000	CFV 6000
Nominal air flow [m ³ /h]		1500	2500	3500	5000	6000
EC fans	phase/voltage [50–60 Hz/VAC]	~1.200/277			~3.380/480	
	power/current [kW/A]	2x0.46/3.0	2x0.74/3.75	2x1.14/1.8	2x1.32/2.1	2x2.6/4.0
	fan speed [min ⁻¹]	2848	2640	2400	1350	1700
	perm. amb. temp. [°C]	-35...+50				
	motor protection	IP54				
	insulation class	F				
	motor sound power level to outlet [dBA]	74	75	76	71	77.6
	SFP @ nominal air flow, max. pressure [kW/(m ³ /s)]	2x1.1	2x1.06	2x1.13	2x0.946	2x1.00
Filter class exhaust/supply standard (optional)	F7 (G4)/F7 (G4)					
Weight (net, without packaging) [kg]	230	250	280	400	530	
Protection class	IP34					
Sound pressure level @ 0.3 m to environment [dBA]	41	43	44	39	46	

HEAT RECOVERY VENTILATION UNIT CFV, CFV-HE, CFV-HW

CFV 1500, CFV 2000

CFV 3500, CFV 5000, CFV 6000


Dimensions [mm]	CFV 1500	CFV 2500	CFV 3500	CFV 5000	CFV 6000
L	1950	1950	2200	2330	2330
W	750	750	890	1390	1390
H	1550	1550	1800	1800	1800
H1	300	300	300	400	400
S	600	600	600	1000	1000
E	170	170	170	170	170



CFV 1500



Sound power Lw in dB

Environment	66	65	62	52	33	53	48	51	59
Outlet	68	69	70	68	65	64	61	58	71
Hz	63	125	250	500	1000	2000	4000	8000	LwA



CFV 2500



Sound power Lw in dB

Environment	63.6	65.5	64.2	58.2	40.1	57.2	52.2	55.4	63
Outlet	65.6	69.5	72.2	74.2	72.1	68.2	65.2	62.4	76.6
Hz	63	125	250	500	1000	2000	4000	8000	LwA

CFV 3500





Sound power Lw in dB

Environment	67	64	66	57	37	59	53	57	64
Outlet	69	68	74	73	69	70	66	64	76
Hz	63	125	250	500	1000	2000	4000	8000	LwA

*External SFP for each fan [kW/(m³/s)]



CFV 5000



Sound power Lw in dB

Environment	66	65	62	52	33	53	48	51	59
Outlet	68	69	70	68	65	64	61	58	71
Hz	63	125	250	500	1000	2000	4000	8000	LwA

CFV 6000



Sound power Lw in dB

Environment	66	65	62	52	33	53	48	51	59
Outlet	68	69	70	68	65	64	61	58	71
Hz	63	125	250	500	1000	2000	4000	8000	LwA

*External SFP for each fan [kW/(m³/s)]